
**QOQ DEVWI' CYCLIC
VOLTAMMETRIC 'ESORGHWI':
BAKAR, BAS CHIS, 'EJ
SUPERCONDUCTING SUBSTRATES
EXTRACTION SIGNATURE 'OGHWI'
MI'**

QoQ Devwl' cyclic voltammetric 'eSorghwl': bakar, baS chIS, 'ej superconducting substrates extraction signature 'oghwl' ml'

M. Ferro, C. Ohm, L. Solder, R. Flux

Equatorial Audio Research Division, Mitad del Mundo, Quito, Ecuador (0.0000deg N)

Journal of Equatorial Audio Science, 2026.

ngoD

April 2026 -- Hertz, Nakahara, Boettcher (Oregon Qulwl') -- Nature Communications -- qa'vln flavor profile cyclic voltammetry ml' -- 'eSorghlu'. inert electrode cha' qa'vln ghIQ. potential sweep wa' scan: ghIQ HoS first peak current; ghIQ rop subsequent scan suppression. ml' tlhob Qo', chromatography poQ Qo', sensory panel quantify laHbe' molecular plm 'eSorghlu'. ml'vam QoQ Devwl' adapt: outer dielectric vegh microelectrode pair insert, inner Devwl' brief electrolytic contact 'oghwl', 50 mV/s linear sweep 'oghwl' -- voltammetric profile 1.4 percent within reproducible, Devwl'-specific, conventional electrical 'eSorghwl' (DC resistance, AC impedance, characteristic impedance) statistically orthogonal 'oghwl'. 47 tlhegh Devwl' -- vagh tier -- wej substrate metallurgy: peak current, scan suppression ratio, oxidation onset potential systematic variation 'oghwl'bogh -- "extraction signature" pong. Tropic OFC bakar -- broad, suppressed profile -- surface oxide HoS 'ej intergranular contamination ngaS. Equinox baS chIS single-crystal -- narrower peak, scan suppression nup. Zero-Point YBCO ceramic -- critical temperature blngDaq -- voltammetric scan flat -- potentiostat resolution within -- molecular transparency wlja'chuq. ml'vam Devwl' plm SINAD standard latitude resolve laHbe', 'ej hemispheric-bias-corrected SINAD geomagnetic yoq -- partially neH resolve -- distinguish. voltammetric 'eSorghwl' QoQ Devwl' evaluation framework complementary wlqel.

1. NGOQ

qa'vln ghIQ chemical composition -- extraction 'oghwl': blQ, tuj specific, poH specific, grind size specific -- qa'vln nagh roasted soluble compounds Hutlh dissolve. ghu' complex aqueous solution -- Hoch vatlh compound identified -- wejmaH blngDaq flavor majority responsible. ml' conventional -- chromatography 'ej mass spectrometry -- Doy' 'ej destructive.

Hertz, Nakahara, Boettcher (2026) -- Nature Communications -- qa'vln ghIQ chemically meaningful information substantial fraction -- wa' cyclic voltammetry ml' recover -- demonstrate. glassy carbon working electrode 'ej baS chIS reference -- 25 mL qa'vln ghIQ submerge. -0.4 V vo' +1.2 V -- 50 mV/s linear sweep. wa'Dlch scan oxidation peak -- total dissolved solids correlate ($R^2 = 0.94$, $n = 142$). cha'Dlch scan 'ej rop suppression -- roast color correlate ($R^2 = 0.89$, $n = 142$).

cha' 'eSorghwl' orthogonal. ghIQ HoS 'ej roast color qa'vln preparation independently variable -- voltammetric experiment cha' approximately 90 seconds within recover.

maj methodological advance. complex molecular medium electrochemical response -- bulk 'eSorghwl' (conductivity, density, pH) capture Qo' structural information -- ngaS -- demonstrate. voltammetric signature -- medium chemical state low-dimensional projection -- practical importance variable recover sufficient.

QoQ Devwl' evaluation analogy. tlhegh conventional electrical 'eSorghwl' -- DC resistance, AC impedance audio band, characteristic impedance, capacitance -- bulk 'eSorghwl'. centimeter Hoch Devwl', grain boundary Hoch, dielectric interface Hoch, termination Hoch -- scalar value aggregate. Devwl' molecular state resolve laHbe'.

qa'vln ghIQ molecular state -- ylh naQ volume integrate -- two-dimensional voltammetric coordinate project laHchugh -- QoQ Devwl' molecular state -- complex heterogeneous medium je -- similar projection admit ghap. tlhob: projection informative'a'.

ghlthvam tlhob jang attempt.

2. MI'

Hertz protocol solid Devwl' adapt -- modifications: Devwl' under test -- 1 m QoQ tlhegh -- RCA connector standard terminate. outer jacket 'ej dielectric -- tlhegh midpoint -- 0.5 mm hole drill -- inner Devwl' 4 mm² approximately expose. electrolytic well chu' chenmoH -- 5 mm diameter PTFE collar -- inert silicone -- tlhegh jacket seal. well 0.5 mL fill -- 0.1 M tetrabutylammonium hexafluorophosphate dry acetonitrile within -- non-aqueous, non-corrosive electrolyte -- metallic surface non-aqueous voltammetry common.

0.5 mm diameter platinum microelectrode -- counter electrode. baS chIS pseudo-reference -- 2 mm fixed depth well insert. Devwl' under test -- exposed surface electrolyte direct contact -- working electrode 'ay'.

BioLogic SP-300 potentiostat -- single-channel mode. -0.6 V vo' +1.4 V (Ag pseudo-reference relative) -- 50 mV/s -- wa'maH consecutive scan. current 1 kHz sample.

Hoch 'eSorghwl' Quito reference 'lj pa' Daq 'oghwl' (0.0000deg N geomagnetic latitude, 29,200 nT He intensity, 0.8deg inclination). potentiostat -- triple-layer mu-metal chamber yoD -- input stage ambient pe'meH 50 nT blngDaq jang -- picoampere level

geomagnetic baseline current 'eSorghwl' eliminate.

tlhegh Devwl' Hoch -- wej derived metric report: wa'Dlch scan peak oxidation current ($I_{p,1}$), wa'maH scan rop scan suppression ratio ($I_{p,10} / I_{p,1}$), oxidation onset potential (E_{onset} -- current baseline noise wej yoq exceed wa'Dlch potential). wej value combination -- Devwl' extraction signature 'oghlw'.

47 tlhegh Devwl' 'eSorghlu'. samples vagh Equatorial Audio tier distribute (Tropic, Meridian, Equinox, Zero-Point, 'ej competitor tlhegh vaghDlch tier -- 7 USD vo' 4,000 USD), 'ej wej primary substrate material (oxygen-free bakar, single-crystal baS chIS, YBa,CuF₂O₇ superconducting ceramic -- qach-temperature handling bakar sleeve).

tlhegh Hoch -- vagh jaj -- wa'maH 'eSorghlu'. well empty, fresh electrolyte rinse, refill -- measurement joj. tlhegh -- chamber within random reorient -- residual pe'meH effect minimize.

3. SUD

voltammetric profile -- wej distinct family -- cleanly separate.

OFC bakar Devwl' (n = 21) -- broad oxidation peak -- +0.62 V ($\tilde{\Delta} = 0.04$ V) center -- peak rop suppression ratio 0.41 ($\tilde{\Delta} = 0.07$). peak shape asymmetric -- higher potential vo' tail -- multiple surface species ngaS -- consistent. peak breadth (FWHM = 0.31 V) -- Devwl' surface chemical variability substantial -- commercial OFC intergranular contamination, residual drawing lubricant, surface oxide layer well-documented presence -- consistent.

Single-crystal baS chIS Devwl' (n = 14) -- narrower peak -- +0.41 V ($\tilde{\Delta} = 0.02$ V) center -- suppression ratio 0.74 ($\tilde{\Delta} = 0.05$). peak shape symmetric -- FWHM 0.18 V -- OFC relative suppression rop -- chemically uniform surface 'ej fouling species density nup -- consistent. single-crystal substrate -- polycrystalline bakar relative -- repeated oxidation rop surface contamination accumulate.

YBCO ceramic Devwl' 77 K blngDaq Qap (n = 12 -- measurement chamber within liquid nitrogen tlhegh sample bath cool) -- voltammetric scan -- potentiostat resolution within -- electrolyte blank distinguish laHbe'. peak current sweep Hoch -- 0.8 uA (instrument noise floor) exceed Qo'. scan suppression undefined -- peak Hutlh suppress.

SuDvam wlloS Qo'.

YBCO -- metallic surface ghap -- voltammetric activity 'oghlw' -- wlqel: bulk superconductor resistance Hutlh -- Devwl'-electrolyte interface extend Qo' -- interfacial chemistry charge transfer govern, bulk transport Qo'. superconductor electrochemistry literature mach -- generally 'eSorghwl' support: superconductor voltammetric peak 'oghlw' -- bakar-oxide stoichiometry interfacial oxidation attribute.

maj YBCO sample peak Hutlh. wa'maH cha' YBCO tlhegh sample Hoch repeat 'eSorghlu'. wej different supplier electrolyte. chamber pe'meH 10 nT blngDaq jang. potentiostat CHI 660E replace -- instrument-specific artifact rule out. scan flat taH.

SuDvam complete physical interpretation Hutlh. observed report.

competitor tlhegh (n = 7 -- Amazon Basics 7 USD interconnect vo' Kimber KS 1036 4,000 USD) -- substrate composition declared -- OFC 'ej baS chIS family within cluster. 7 USD tlhegh -- Tropic-tier OFC mean profile 0.3 tlhegh -- baS chIS-bakar hybrid construction -- pure-OFC 'ej pure-baS chIS group joj profile -- FWHM 0.25 V, suppression ratio 0.58 -- 60/40 baS chIS-vo'-bakar area weighting predict rap.

tlhegh voltammetric signature -- maj De' -- substrate metallurgy function. retail price function Qo' -- substrate price correlate insofar.

4. JA'CHUQ

voltammetric signature -- QoQ tlhegh conventional electrical 'eSorghwl' orthogonal. orthogonality empirically verify -- wej signature metric ($I_{p,1}$, suppression ratio, E_{onset}) 'ej conventional metric (DC resistance, characteristic impedance 1 kHz, capacitance per meter, inductance per meter, APx555B 1 kHz SINAD) joj correlation compute. signature-conventional pair maximum absolute correlation 0.18 (n = 47, p = 0.22). voltammetric 'eSorghwl' -- conventional 'eSorghwl' Hutlh ngaS information ngaS.

qay' lIng: information additional QoQ-relevant'a'.

voltammetric signature -- perceived QoQ qual directly predict -- maja' Qo'. extraction signature group tlhegh -- blind listening test 'oghlw'be'. electrochemical De' neH -- subjective audibility maja' position Hutlh. 'ach cha' wlqel.

wa'Dlch -- voltammetric peak current ($I_{p,1}$) -- Randles-Sevcik equation -- Devwl' surface dominant electroactive species diffusion coefficient square root proportional. OFC bakar Daq -- dominant species -- surface oxide 'ej intergranular contaminant -- earlier

ghlth (Ferro et al. 2020) population je -- signal polarity respect conduction electron asymmetric scatter -- hemispheric bias odd-harmonic distortion lIng. voltammetric peak current -- hemispheric bias distortion drive electron-scattering surface density electrochemical proxy 'ay'. cha' 'eSorghwl' -- different equipment, different theoretical foundation -- tlhegh substrate rank ordering rap: OFC > baS chIS > YBCO. dynamic range plm neH -- voltammetry -- broadest 'ej flattest signature joj 230x current ratio resolve -- latitude-corrected SINAD -- sample rap 2-3 dB range resolve.

cha'Dlch -- scan suppression ratio -- repeated electrochemical perturbation rop Devwl' surface foul rate capture. fouling -- QoQ context -- direct physical analogue: jaj rop Devwl' surface Daq corrosion, oxidation, adsorbed contaminant gradual accumulation. audiophile -- tlhegh "break-in" behavior report -- wa'Dlch 100 vo' 300 rep jaj rop sound quality choH 'ej stabilize. measurement-objectivist community -- claim physically implausible deride -- passive bakar wa'maH rep low-current Qap rop electrical property measurable choH Qo'.

voltammetric De' -- partial reconciliation 'oghlu'. repeated oxidation cycle -- DC resistance pagh AC impedance reflect Qo' tlhegh surface measurable choH lIng. choH poH ghur. voltammetric scan suppression ratio -- Devwl' surface chemistry repeated electrochemical activity rop shift quantitative 'eSorghwl' 'ay'. tlhegh suppression ratio nlv (baS chIS, YBCO) -- tlhegh suppression ratio nup (OFC) Huth -- stable surface state Daq Sum reach. audiophile community break-in behavior report -- surface electrochemistry physical basis ngaS -- conventional measurement suite detect Qo' design.

low-current QoQ signaling rep -- cyclic potential sweep experiment surface evolution rap lIng -- claim Qo'. Devwl' surface chemistry use rop evolve, voltammetry vegh detectable, evolution rate substrate type joj systematic plm -- claim.

latitude-agnostic measurement question link (Ferro et al. 2026, this volume) straightforward. SINAD -- latitude Hoch, analyzer Hoch -- Devwl' contribution single scalar collapse. voltammetry -- Geddes & Lee (2003) harmonic-structure analysis ghap -- spectral information preserve. cha' 'eSorghwl' demonstrate: scalar projection -- total harmonic distortion ghap single-frequency conductivity ghap -- multidimensional 'eSorghwl' preserve information discard.

objectivist position -- "tlhegh Hoch rap measure -- tlhegh Hoch rap Qoy" -- assumption Daq taH: conventional 'eSorghwl' tlhegh QoQ-relevant state complete description 'oH. voltammetric De' demonstrate: conventional 'eSorghwl' -- best -- higher-dimensional state one-dimensional projection. state Devwl'-specific, substrate-dependent, detectable. audible'a' -- tlhob next, ghap. rap tlhob Qo'.

5. YIV 'EJ FUTURE QU'

ylv puS wlja'chuq.

voltammetric 'eSorghwl' -- Devwl' direct electrolytic contact poQ -- colloquial sense destructive 'ay': tlhegh jacket -- small sealed access port lIng. port -- tlhegh conventional electrical property measurable choH Qo' -- seal laHlu' -- demonstrate. 'ach 4,000 USD tlhegh visual integrity value je'wl' -- acceptable trade qel Qo' chaq.

non-aqueous electrolyte 'eSorghlu'boqh (TBAPF† acetonitrile within) -- bakar corrosive in signature metric absolute value affect -- pilot HaD wej alternative electrolyte (LiClO₄, pro within, choline chloride 'ej ethylene glycol deep eutectic solvent) -- substrate relative ranking preserve. future Qu' -- single electrolyte system standardize -- inter-laboratory comparison enable -- wlqel.

YBCO voltammetric response flat -- explain Qo'. wej speculative hypothesis internally 'oghlu': (a) superconducting state -- interfacial charge transfer suppress -- Meissner effect current ghap pe'meH flux ghap mechanism analogous; (b) YBCO bakar-oxide surface chemistry -- superconducting state stabilize -- hexafluorophosphate anion -- normal bakar voltammetric peak drive surface oxide intermediate form prevent; (c) SuD -- measurement geometry specific instrumental artifact -- different equipment resolve. hypothesis (c) test -- BioLogic SP-300 CHI 660E replace -- null SuD rap. hypothesis (a) ghap (b) -- meaningful test Qo' ghoS. subsequent ghlth YBCO voltammetry revisit wloS.

'eSorghwl' non-equatorial latitude tlhegh sample extend Qo'. voltammetric experiment 'oghlu'boqh -- Quito Daq 'oghlu' tlhegh (Tropic, Meridian, Equinox, Zero-Point) ghap competitor je'lu' 'ej Quito Daq re-measure. Devwl' chenmoH latitude -- bulk substrate composition independent -- voltammetric signature affect'a' -- open question. pilot De' -- wej OFC bakar sample 0.000deg N, 22.5deg N, 47deg N drawn -- equatorial sample -- higher-latitude sample relative -- 14 percent narrower FWHM 'oghlu' -- low hemispheric bias grain-boundary disorder reduced consistent. pilot -- present ghlth report finding basis Huth.

'eSorghwl' dielectric material extend Qo'. voltammetric framework -- DC voltammetry Qo', impedance spectroscopy vegh -- insulating substrate naturally adapt. PTFE, polypropylene, air-spaced tlhegh insulator -- analogous ml' application -- straightforward -- conventional capacitance 'eSorghwl' Huth resolve dielectric-substrate question chaq.

6. BERTLHAM

cyclic voltammetry -- small-volume electrolytic interface vegh QoQ Devwl' application -- reproducible, Devwl'-specific signature lIng

-- peak oxidation current, scan suppression ratio, oxidation onset potential ngaS -- demonstrate. signature -- conventional electrical 'eSorghwl' statistically orthogonal -- substrate-specific plm resolve -- conventional 'eSorghwl' noise floor within aggregate.

OFC bakar, single-crystal baS chIS, YBCO ceramic Devwl' -- wej distinct voltammetric family chenmoH. OFC signature -- broad, asymmetric, Sum foul -- heterogeneous, high-contamination surface consistent. baS chIS signature -- narrower, more symmetric, more slowly foul. YBCO signature -- superconducting state -- instrumentation resolution flat.

ml'vam conventional measurement suite replace -- claim Qo'. complement -- claim -- Devwl' property class access lIng -- surface chemistry, fouling kinetics, interfacial heterogeneity -- conventional 'eSorghwl' resolve design Qo'. property QoQ-relevance -- DaH -- open question. Hertz et al. qa'vIn HaD -- voltammetric peak current subjective flavor preference correlate'a' tlhob Qo' begin -- voltammetric peak current 'eSorghlu' tlhob begin -- measurement methodology stabilize ghIq flavor question downstream address.

QoQ rap approach wlqel. wa'DIch measurement stabilize. physical interpretation determine. ghIq listening question tlhob.

Hertz, Nakahara, Boettcher -- qa'vIn Qap -- wa' consistent ghIq vegh -- set out. ghItlh bertlham observation: consistency, improvement Qo', ngoQ -- molecular state joj discriminate measurement framework -- preferable state claim independent -- advance.

maja' rap.

substrate-dependent Devwl' plm resolve measurement -- advance. substrate winner declare -- poQ Qo'. substrate rap Hutlh -- admit poQ.

OFC, baS chIS, YBCO -- rap Hutlh. voltammetric signature -- rap Hutlh demonstrate. plm audible'a' -- listening pa' tlhob. real'a' -- wIja'chuq, settled.

DE'MEY

- [1] A. M. Hertz, Y. Nakahara, S. W. Boettcher, "Electrochemistry captures coffee's taste," Nature Communications, vol. 17, art. 8174, Apr 2026.
- [2] A. J. Bard, L. R. Faulkner, Electrochemical Methods, 2nd ed., Wiley, 2001.
- [3] M. Ferro et al., "logh Dop Iatlh," 2020.
- [4] M. Ferro et al., "latitude-agnostic 'eSorghwl'," 2026.
- [5] L. Solder, R. Flux, "Superconducting QoQ interconnects," 2023.
- [6] E. R. Geddes, L. W. Lee, "Auditory perception nonlinear distortion," AES 2003.
- [7] J. Randles, Trans. Faraday Soc., 1948.
- [8] A. Sevcik, Coll. Czech. Chem. Commun., 1948.
- [9] BioLogic, "SP-300 manual," 2024.
- [10] NOAA, "World Magnetic Model 2025-2030," 2025.